















1 Bin Activator BA-210 BAEX-210



10 WAMAIR® Dust Collectors FP-210 / FPX-210



Maintenance-friendly

2 BINSWEEP® Rotary Dischargers BSN



Height-saving discharge

11 Rotary Level Indicators ILT



Easy to install

3 Tapered Twin Shaft Screw Feeders BU



Mass flow discharging & feeding

12 Micro-Batch Feeders MBF-210



Process reliability

4 Waste Bag Compactors COM



Clean work environment & operator safety

13 Trough Screw Conveyors MSC




Easy access for cleaning

5 Loss-In-Weight Screw Feeders DCC



Highly reliable and easy to clean

14 Live Bin Bottoms MU



Ideal for discharging bran or middlings

6 Diverter Valves DVA



Dustproof

15 External Electric Vibrators IME-210



ATEX zone 22-compliant

7 EXTRABEND® & EXTRACURVE® Pipe Elbows



Abrasion-resistant lightweight design

16 External Pneumatic Vibrators OT-Type



Durable

8 Bucket Elevators EF-EC



Maximum work safety, ATEX zone 22-compliant

9 WAMFLO® Dust Collectors FN-210 and FX-210



Compliant with ATEX and latest health & safety standards

19 Drop-Through Rotary Valves RV/RVR



Versatile in all applications

20 Blow-Through Rotary Valves RVS



Easy access to internal parts

21 Chain Conveyors TCG



Sturdy design

22 Tapered Single-Shaft Screw Feeders UM



Minimum-residue design

23 Diverter Valves VAD



Easy to install, compact design

24 Diverter Valves VAR



Contamination-free

25 Vibrating Bin Aerators VB



For all powdery materials

26 Butterfly Valves VFS



Maintenance-friendly: small number of components

27 Slide Valves VG



High flow rates

28 Slide Valves VL



No seal adjustment required

29 Pinch Valves VM



Easy sleeve replacement

30 Batch-Type Single Shaft Mixers with Bomb Bay Discharge WBH



Short mixing and discharge time

31 Continuous Single Shaft Mixers WAH



High productivity

32 Ribbon Blenders WBN



Gentle mixing

33 BELLOJET® Tanker Loading Bellows ZA



Built-in low-profile dust collector

34 Tanker Loading Bellows ZG



No waste material during loading

35 Tubular Trough Screw Conveyors & Feeders CAO



Minimum-residue design

36 VCP Spring-Loaded Pressure Relief Valves



Maximum work safety: ATEX zone 21-certified

# APPLICATIONS





MAC 7.0.IT 09/10 Rights reserved to modify technical specifications.



[www.wamgroup.com](http://www.wamgroup.com)